

NEW 2014 R-VALUES

HUNTER PANELS FLAT POLYISO

H-SHIELD • H-SHIELD CG

RED INDICATES JULY 2014 CHANGE

Size	R-Value	PCS	4X8 SF
0.5		96	3072
1.0	5.7	48	1536
1.1	6.3	43	1376
1.2	6.8	40	1280
1.3	7.4	36	1152
1.4	8.0	34	1088
1.5	8.6	32	1024
1.6	9.1	30	960
1.7	9.7	28	896
1.75	10.0	27	864
1.8	10.3	26	832
1.9	10.8	25	800
2.0	11.4	24	768
2.1	12.0	22	704
2.2	12.6	21	672
2.3	13.2	20	640
2.4	13.8	20	640
2.5	14.4	19	608
2.6	15.0	18	576
2.7	15.6	17	544
2.8	16.2	17	544
2.9	16.8	16	512
3.0	17.4	16	512
3.1	18.0	15	480
3.2	18.6	15	480
3.3	19.2	14	448
3.4	19.9	14	448
3.5	20.5	13	416
3.6	21.1	13	416
3.7	21.7	12	384
3.8	22.3	12	384
3.9	23.0	12	384
4.0	23.6	12	384
4.1	24.2	11	352
4.2	24.9	11	352
4.3	25.5	11	352
4.4	26.1	10	320
4.5	26.8	10	320

HUNTER
Energy Smart Polyiso

HUNTERPANELS.COM
888.746.1114



0714

BASED ON ASTM C1289-11A

HUNTER LOADING

TAPERED PANELS 48" X 48"

SLOPE	PANEL DESIGNATION	DIMENSIONS	BD FT PER PANEL	PCS
1/8	AA	.5" - 1"	12	64
	A	1" - 1.5"	20	38
	B	1.5" - 2"	28	26
	C	2" - 2.5"	36	20
	D	2.5" - 3"	44	16
	E	3" - 3.5"	52	14
	F	3.5" - 4"	60	12
	FF	4.0" - 4.5"	68	10
1/4	X	.5" - 1.5"	16	48
	Y	1.5" - 2.5"	32	24
	Z	2.5" - 3.5"	48	16
	ZZ	3.5" - 4.5"	64	12
	G	1" - 2"	24	32
	H	2" - 3"	40	18
	I	3" - 4"	56	12
1/2	Q	.5" - 2.5"	24	32
	QQ	2.5" - 4.5"	56	12
	XX	1" - 3"	32	24
3/16	JJ	.5" - 1.25"	14	54
	KK	1.25" - 2"	26	28
	LL	2" - 2.75"	38	20
	MM	2.75" - 3.5"	50	14
	J	1" - 1.75"	22	34
	K	1.75" - 2.5"	34	22
	L	2.5" - 3.25"	46	16
	M	3.25" - 4"	58	12
3/8	SS	.5" - 2"	20	38
	TT	2" - 3.5"	44	16
	S	1" - 2.5"	28	26
	T	2.5" - 4"	52	14
1/16	1	.5" - .75"	10	76
	2	.75" - 1"	14	54
	3	1" - 1.25"	18	42
	4	1.25" - 1.5"	22	34
	5	1.5" - 1.75"	26	28
	6	1.75" - 2"	30	24
	7	2" - 2.25"	34	22
	8	2.25" - 2.5"	38	20